



imagePROGRAF TM-240

PERFORMANCE REIMAGINED

Reimagine printing performance with the sustainable 24" imagePROGRAF TM-240, offering less noise printing, more intuitive functionality and brilliant image quality. Seamlessly produce sharp, crisp lines and vivid red colour for eye-catching marketing materials and accurate CAD prints for AEC offices, retail and education.

- **Enhanced professional quality**
The new magenta ink produces a more brilliant red and stable image enhancements mean crisper lines. Print vivid and accurate CAD drawings, posters, educational materials and more
- **Reliable productivity**
Productivity that you can count on, with reliable performance, faster processing time and a quick return from sleep mode. Save time trimming excess margins with borderless print, giving full bleed images of any size, straight from the device
- **Intuitive functionality**
Functional design with a 4.3" touch screen panel displaying intuitive instructions and important information, like media type, remaining media and ink amount. Roll paper can be replaced with ease on the flat-top cover
- **Improved sustainability**
Environmentally conscious EPEAT Gold* rated device for low energy consumption, with power reduction during standby and packaging free from polystyrene foam. Less noise printing makes it ideal for quiet offices

*EPEAT Gold registered in the U.S.

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF™-240

PRINTER TECHNOLOGY

Printer Type	5 Colours 24"
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Print Resolution	2,400 x 1,200 dpi
Number of Nozzles	Total : 15360 nozzles MBK : 5120 nozzles BK, C, M, Y: 2560 nozzles each
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.
Nozzle Pitch	1,200 dpi x 2 lines
Ink Droplet Size	minimum 5pl per colour
Ink Capacity	Bundled Starter Ink: 300ml (80ml for MBK, 55mlx4 for BK, C, M, Y) Sales Ink: 55ml (MBK, BK, C, M, Y)
Ink Type	Pigment inks : 5 colours MBK/BK/C/M/Y
OS Compatibility	32 Bit: Windows 7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 Apple Macintosh: macOS 10.15.7-macOS 13

Others supported job submission protocol

Printer Languages	HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)
Standard Interfaces	USB A Port: N/A USB B Port: Hi-Speed USB Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/IEEE802.3 (10BASE-T) Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b

*Please refer to user manual how to activate/deactivate the wireless LAN

MEMORY

Standard Memory	2GB
Expansion slot	No
Hard Drive	N/A

PRINTING SPEED

CAD Drawing	
Plain paper (A1):	0:23 (Fast Economy Model) 0:25 (Fast) 0:51 (Standard)
Poster:	
Plain Paper (A1):	0:25 (Fast Economy Model) 0:25 (Fast) 0:49 (Standard)
Heavy coated paper (A1):	0:56 (Fast) 1:45 (Standard)

MEDIA HANDLING

Media Feed and Output	Roll Paper : One Roll, Upper-loading, Front Output Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 203.2 - 610mm Cut sheet: 210 - 610mm
Media Thickness	Roll/Cut : 0.07mm - 0.8mm
Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 279.4mm
Maximum Printable Length	Roll paper : 18m (varies according to the OS and application) Cut sheet : 1.6m
Maximum Media Roll Diameter	150 mm
Media Core Size	Internal diameter of roll core: 2"/3" (Optional)
Margins Recommended area	Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm Cut sheet(AppleAirPrint): Top: 20mm, Bottom: 31mm, Side: 3mm Cut sheet (Others): Top: 20mm, Bottom: 20mm, Side: 3mm

Margins Printable area

Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm
Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm
Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm
Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm

Media Feed Capacity

Roll Paper: One roll
Cut Sheet: 1 sheet

Borderless Printing Width (Roll Only)

[Recommended] 515mm(JIS B2), 728mm(JIS B1), 594mm (ISO A1), 10", 14", 17", 24"

[Printable] 257mm(JIS B4), 297mm (ISO A3), 329mm (ISO A3+), 420mm(ISO A2), 515mm (JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm

Other than above, free size borderless printing is supported on only roll paper by user definition
Standard position - 1 sheet

Maximum number of delivered prints

POWER AND OPERATING REQUIREMENTS

Power Supply

AC 100-240V (50-60Hz)

Power Consumption

Operation: 59W or less
Sleep mode: 2.2W or less
Default setting for the time to enter the Sleep mode: Approx. 5 minutes
Power off: 0.1W or less

Operating Environment

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Acoustic Noise (Power/Pressure)

Operation: Approx. 39dB(A) (Standard Plain Paper, Standard mode, Line Drawing/Text mode)
(Measured based on ISO7779 standard)

Standby: 35 dB(A) or less

Operation: 6.0 Bels or less (Standard Plain Paper, Standard mode, Line Drawing/Text mode)
(Measured based on ISO7779 standard)

Regulations

CE mark, UKCA mark

Environment Certificates

CB certification, EPEAT GOLD¹⁾

DIMENSIONS AND WEIGHT

Physical Dimensions and Weight

W x D x H
Main unit + Stand + Basket (SD-24)
978 x 868 x 1060 mm
(Operation panel is not tilted up/Basket Opened)
978 x 756 x 1060 mm
(Operation panel is not tilted up/Basket Closed)
50.9 kg
(including Roll Holder Set, excluding ink and print head)

Packaged Dimensions and Weight

Printer (Main unit with pallet): 1152 x 912 x 679 mm, 71kg
Stand + Basket (SD-24): 1058 x 826 x 270 mm, 20kg

WHAT'S INCLUDED

What's in the Box?

Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Notice for PosterArtist WEB

Software Included

Software available as Download from Web

OPTIONS

Optional Items

Stand Basket (Simple Basket): SD-24
2"/3" Roll Holder: RH2-28
IC Card Reader Holder: RA-02

CONSUMABLES

User Replaceable Items

Ink Tank: M: PFI-031(55ml), MBK/BK/C/Y:PFI-030(55ml)
Print Head: PF-06
Cutter Blade: CT-08
Maintenance Cartridge: MC-31

¹⁾ EPEAT Gold registered in the U.S.

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2023